



# MINI-VIEW POLYCARBONATE ROLLER SHUTTERS



GRA22296 v3.indd 1 24/05/10 11:16 AM

# MINI-VIEW POLYCARBONATE ROLLER SHUTTERS

Maverick Mini-view polycarbonate roller shutters are suitable for a wide range of commercial, industrial and domestic applications with either internal or external installations including: shopping centres, shop fronts, counter tops, arcades, servery's, clubs, doorways, verandas, or any area where visibility is essential whilst providing security against theft or damage from dust and vermin and with the added advantage of the discrete pelmet boxes where headroom is at a minimum.

# **SPECIFICATIONS**

# Size

Each individual Mini-view polycarbonate roller shutter can be manufactured up to a width of 3.6m or a total of 9 square metres.

### Curtain

The curtain is manufactured by alternating and interlocking 50mm x 1.5mm clear polycarbonate slats with 36mm extruded aluminium slats, in 6063-T5 alloy to form a continues hinge. Each joining slat is fitted with moulded nylon end clips to prevent lateral movement and provide a smooth and quiet operation inside the side guides.

#### **Bottom Rail**

The bottom rail of the shutter is manufactured from an extruded aluminium section 65mm × 10mm which shall encase a locking device. Optional felt brush available.

# Locking

The bottom rail houses a keyed centre lock within the extrusion. This operates 15mm × 2mm aluminium flat bars which, when in the locked position, secure into the side guides on both sides of the opening. The standard locking position allows for double sided lock with operation from both inside and out.

# Side Guides

The guides are manufactured from extruded aluminium sections 53mm deep x 25mm wide, 62mm deep x 25mm wide or Heavy Duty 72mm deep x 27mm wide. Optional felt brush available.

#### **Brackets**

Manufactured from slotted 90mm x 40mm mild steel.

#### **Pelmet boxes**

All Mini-view polycarbonate roller shutters can be enclosed in a various number of different size pelmet boxes from 150mm up to 250mm.

### Drum

The drum is manufactured from 60mm diameter hexagonal tube and shall be fitted with helical coil springs designed to counterbalance the curtain weight throughout its full operation.

# **Operation**

Manual operation, simply push up and pull down with supplied pull pole. Doors can be electrically motorised with various push button, remote control or key switch operation.

# **Finish**

Clear anodised standard colour Powder coating as an option in Dulux powder coat range.

Maverick Roller Products Pty Ltd is continually researching and developing its products and reserves the right to change specifications without notice.

MINI-VIEW ALUMINIUM ROLLER SHUTTERS										
Drum Options	Height mm	1200	1500	1800	2100	2400	2700	3000	3300	3600
60mm Drum	Roll Diameter	140	165	170	180	185	195	205	230	250
130mm Drum	Roll Diameter	190	200	205	220	235	250	265	280	290



2/52 Alfred Road Chipping Norton NSW 2170 Ph: 02 9755 4055 Fax: 02 9755 0427 Web: www.maverickrollerproducts.com.au Email: info@maverickrollerproducts.com.au

50mm 50mm 10mm 25mm Standard Heavy Duty 3RA22296 5/10